



The Chemical Company

# Masterflex<sup>®</sup> Primers 1 & 2

## Primers for use with Masterflex<sup>®</sup> series sealants

### Description

Masterflex<sup>®</sup> Primer No1 & 2

Liquid primers used in the preparation of joint surfaces prior to the use of Masterflex<sup>®</sup> 700 series of sealants.

Masterflex<sup>®</sup> Primer No1 is used when preparing porous surfaces such as concrete, brickwork, stonework, asbestos and timber.

Masterflex<sup>®</sup> Primer No2 is used when preparing non-porous surfaces such as glass, stainless steel and ceramics.

### Application temperature

5°C to 40°C.

### Coverage

Masterflex<sup>®</sup> Primer No1

8m<sup>2</sup> per litre depending on porosity.

Masterflex<sup>®</sup> Primer No2

40m<sup>2</sup> per litre approximately.

### Caution

Due to the penetrating and sealing action of Masterflex<sup>®</sup> Primers, staining may occur on materials such as granite, marble, natural stone and man made composites. If in doubt consult BASF Construction Chemicals SA's Technical Services Department.

### Directions for use

#### Preparation of surfaces

Joint faces to be primed must be completely dry and free from all dirt, dust, cement laitance and other loose and deleterious matter. This is best achieved by grit or sand blasting or thorough wire brushing and then blowing clean with oil free compressed air.

### Application

Pour a small amount of the primer into a clean container ensuring that the main container is tightly resealed. Liberally apply a coat of primer with a soft brush to the required surface. Allow to become tack free before installing Masterflex<sup>®</sup> sealants. If primer is left for more than 3 hours re-priming is necessary. Note: Masterflex<sup>®</sup> Primers are solvent-based.

### Equipment care

Clean all brushes immediately with Cleaning Solvent.

### Packaging

Masterflex<sup>®</sup> Primer No1 is available in 500 ml tins.

### Storage

Store under cover, out of direct sunlight and protect from extremes of temperatures.

Failure to comply with the recommended storage conditions may result in premature deterioration of the product or packaging. For specific storage advice consult BASF Construction Chemicals SA's Technical Services Department.

### Safety precautions

As with all chemical products, care should be taken during use and storage to avoid contact with eyes, mouth, skin and foodstuffs (which can also be tainted with vapour until product fully cured or dried). Treat splashes to eyes and skin immediately. If accidentally ingested, seek immediate medical attention. Keep away from children and animals. Reseal containers after use.



The Chemical Company

# Masterflex<sup>®</sup> Primers 1 & 2

## Note

Field service, where provided, does not constitute supervisory responsibility. For additional information contact your local BASF Construction Chemicals SA representative. BASF Construction Chemicals SA. reserves the right to have the true cause of any difficulty determined by accepted test methods

## Quality and care

All products originating from BASF Construction Chemicals' SA facility are manufactured under a management system independently certified to conform to the requirements of the quality, environmental and occupational health & safety standards ISO 9001:2000.

---

Whilst any information contained herein is true, accurate and represents our best knowledge and experience, no warranty is given or implied with any recommendations made by us, our representatives or distributors, as the conditions of use and the competence of any labour involved in the application are beyond our control.

---

As all BASF's technical datasheets are updated on a regular basis it is the user's responsibility to obtain the most recent issue.

---

## **BASF Construction Chemicals South Africa (Pty) Ltd**

P.O. Box 420, Westonaria, 1780  
11 Pullinger Street, Westonaria, 1779  
Tel: +27 11 754 1343  
Fax: +27 11 754 1105

852 Sixteenth Road, Midrand  
PO Box 2801, Halfway House, 1685  
Tel: +27 11 203 2405

Website : [basf-cc.co.za](http://basf-cc.co.za)

